



# YYCW.MH18376 Exhaust Hoods Without Exhaust Dampers

[Page Bottom](#)

## Exhaust Hoods Without Exhaust Dampers

See General Information for Exhaust Hoods Without Exhaust Dampers

**STREIVOR INC, DBA STREIVOR AIR SYSTEMS**

MH18376

2150 Kitty Hawk Rd  
Livermore, CA 94551 USA

Model	Length Ft	Air Flow cu Ft/Min/Ft of Hood Length *		Max Cooking Surface Temp F
		Min Exhaust	Max Supply #	
IS150	3-21	150	N/A	400
IS200	3-21	200	N/A	450
IS275	3-21	275	N/A	600
WC150	3-21	150	N/A	400
WC200	3-21	200	N/A	450
WC275	3-21	275	N/A	600
WC325	4-21	325	N/A	700
EC150	3-21	150	N/A	400
EC300	3-21	300	N/A	600
EC325	4-21	325	N/A	700
ICBD300	3-21	300	N/A	400
ICBD325	4-21	325	N/A	450
ICBD425	4-21	425	N/A	600
ICBD475	4-21	475	N/A	700
WCLC150	3-21	150	N/A	400
WCLC200	4-21	200	N/A	450
WCLC300	4-21	300	N/A	600
WCAF150	3-21	150	N/A	400
WCAF200	4-21	200	N/A	450
WCAF300	4-21	300	N/A	600
WCBD150	3-21	150	N/A	400
WCBD200	4-21	200	N/A	450
WCBD250	4-21	250	N/A	600
WCBD300	4-21	300	N/A	700

CJ-WCBD (*), SACP80 (+)	4-16.75	80	25	400
CJ-WCBD, SA120	4-16.75	120	25	400
CJ-WCBD (*), SACP160 (+)	4-16.75	160	25	600
CJ-WCBD, SACP180	4-16.75	180	25	600
WCFS150	3-21	150	N/A	400
WCFS200	4-21	200	N/A	450
WCFS250	4-21	250	N/A	600
WCFS300	4-21	300	N/A	700
CWCD150	4-21	150	105	400
CWCD200	4-21	200	125	450
CWCD250	4-21	250	125	600
CWCI150	4-21	150	105	400
CWCI200	4-21	200	125	450
CWCI250	4-21	250	125	600
CWCC150	4-21	150	105	400
CWCC200	4-21	200	125	450
CWCC250	4-21	250	125	600
LPPO170	3-21	170	N/A	450
LPPO200	3-21	200	N/A	600
LPSD170	3-21	170	N/A	450
LPSD200	3-21	200	N/A	600
ICFS 300	4-21	300	N/A	400
ICFS 325	4-21	325	N/A	450
ICF 425	4-21	425	N/A	600
ICFS 475	4-21	475	N/A	700
ICDS 300	4-21	300	N/A	400
ICDS325	4-21	325	N/A	450
ICDS425	4-21	425	N/A	600
ICDS475	4-21	475	N/A	700
LCFS 150	3-21	150	N/A	400
LCFS 200	4-21	200	N/A	450
LCFS 300	4-21	300	N/A	600

\*Air flow rates are established under draft free laboratory conditions with the appliance cooking surface temperature as noted. Greater exhaust and/or lesser supply air flow rates may be required for each specific installation to obtain complete vapor and smoke removal.

#Directed into the hood and/or out the bottom.

(\*) - With optional containment panels installed.

(+) - Provided with containment panels.

Last Updated on 2009-12-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".