



Item # _____

CKV LED Surface Mounted Hood Light

Model: CKV-SM-HL



- **E-Z mount feature** allows for quick installation
- **Gaskets** permanently affixed save installation time
- **U.L. Listed and C.S.A. certified** for use in commercial cooking hoods
- **Meets all requirements** for NFPA 96 and N.E.C. 410
- **Designed for Convenient installation** to prewired hoods
- **Greaseproof, Waterproof construction**
- **Aluminum fixtures** are furnished with a brushed finish to match stainless steel hood interiors

MODEL NO.	DESCRIPTION
CKV-SM-HL-F	Die cast aluminum with porcelain body fixture
CKV-SM-HL-G	Thermal and shock resistant tempered glass globe
CKV-SM-HL-WC	Wire cage accessory

SPECIFICATIONS

- **FIXTURE BODY** - Die cast aluminum with brushed finish
- **SOCKET** - Porcelain body and copper shell
- **WIRE LEADS** - 16 AWG, 6" (152mm) long
- **GROUND LEAD** - 6" (152mm) long green colored 18 AWG wire
- **WATTAGE** - Accepts standard 100 watt A19 bulb (not furnished)
- **VOLTAGE** - Rated up to 120 volts
- **GASKETS** - Silicone
- **GLOBES** - Clear, thermal and shock resistant tempered glass
- **WIRE GUARD** - Plated steel
- **OVERALL SIZE** - 5-1/2" (140mm) diameter and 8-3/4" (222mm) long with wire guard
- **JUNCTION BOX** - Not furnished. Fixture is designed to accept any standard 3 1/2" (89mm) or 4" (102mm) junction box

